# MILLIOHM METER

Model: MO-2002 *ISO-9001, CE, IEC1010* 







### **FEATURES**

- \* 4 terminal devices for accurate measurement of very low resistance.
- \* Ideal for measuring the resistance of components precisely.
- \* Wide measuring range, 0.01 m ohm 20K ohm, 7 ranges.
- \* 20 mm, large size LED display.
- \* Built-in over input protection.
- \* Durable bench type housing case.
- \* Built-in over input protection.

The Art of Measurement

### Bench type

## **MILLIOHM METER**

Model: MO-2002

#### **FEATURES**

- \* 4 terminal devices for accurate measurement of very low resistance.
- \* Ideal for measuring the resistance of components precisely.
- \* Ideal for testing protective conductors, lightning conductors and welded points.
- \* Wide measuring range, 0.01 m ohm 20K ohm, 7 ranges.
- \* 20 mm, large size LED display, easy read-out.
- \* LSI circuit provides high accuracy, reliability and durability.
- \* Built-in over input protection.
- \* Durable bench type housing plastic case stand.
- \* Built-in over input protection.

GENERAL SPECIFICATIONS			
Test Range	20 m ohm ( 1 A DC )		
(Test Current)	200 m ohm ( 1 A DC )		
	2 ohm ( 100 mA DC )		
	20 ohm ( 10 mA DC )		
	200 ohm ( 1 mA DC )		
	2 K ohm ( 100 uA DC )		
	20 K ohm ( 10 uA DC )		
Warning Setup	* Warning LED Indicator		
	* Buzzer		
Operating Temp.	0 to 50 °C ( 32 to 122 °F ).		
Operating Humidity	Less than 80 % R.H		
Power Supply	AC 110V ± 15%, 50/60 Hz		
	or AC 230V ± 15%, 50/60 Hz.		
Fuse for Power	* 200 mA/250 V		
Supply	* Size : 5 X 20 mm dia		
Dimension	nsion 280 x 210 x 90 mm		
	( 11.0 x 8.3 x 3.5 inch)		
Weight	Approx. 2.2 Kg ( 4.85 LB ).		
Standard	Power Cord 1 PC.		
Accessories 4 wire with 2 Kelvin clips 1 pair.			
	Instruction Manual 1 PC.		

ELECTRICAL SPECIFICATIONS (23 ± 5 °C )					
Range	Resolution	Test current	Accuracy		
20 m ohm	0.01 m ohm	1 A	± (0.2 % + 6 d)		
200 m ohm	0.1 m ohm	1 A			
2 ohm	1 m ohm	100 mA			
20 ohm	0.01 ohm	10 mA	± (0.2 % + 4 d)		
200 ohm	0.1 ohm	1 mA			
2 K ohm	0.001 K ohm	100 uA			
20 K ohm	0.01 K ohm	10 uA			
@ The above	accuracy is based on th	e reading value.			
Range	Open Circuit Voltage				
20 m ohm	Approx. DC 4.5 V				
200 m ohm	Approx. DC 4.5 V				
2 ohm	Approx. DC 4.5 V				
20 ohm	Approx. DC 4.1 V				
200 ohm	Approx. DC 3.3 V				
2 K ohm	Approx. DC 2.7 V				
20 K ohm	Approx. DC 1.9 V				

<sup>\*</sup> Appearance and specifications listed in this brochure are subject to change without notice.