



CM-03

AC Leakage Current Tester

UL

CE CAT II 600V, CAT III 300V

Features:

- Accurate AC digital clamp meter for **leakage current** measurement
- AC current measurement: **0 ~ 60A**
- AC voltage measurement: **0 ~ 400V**
- **10 μ A** ultra high resolution on 40mA range
- Shield transformer jaws to minimize the effect of external stray magnetic field.
- Large jaw with **30 mm** diameter.
- **ACA Five Ranges** (40mA, 400mA, 4A, 40A, 60A) for all application.
- A filter circuit is designed to eliminate the effect of high frequency noise and harmonics for AC current measurement.
- Large **3 3/4 digits** LCD
- Fast bargraph display (**30 times/sec.**) for transient observation.
- **Continuity** and **Frequency** measurements.
- **Max/Min**, Data **Hold** functions, and **Relative** Measurement
- Easy single rotary switch for any function selection
- **600V** overload protection for **ohm** measurement

Electrical Specifications: (23°C \pm 5°C)

AC Current:

Range	Resolution	Accuracy		Remarks
		50/60 Hz	Wide (40 - 1KHz)	
40mA	10 μ A	$\pm 1.0\% \pm 3$ dgts	$\pm 2.0\% \pm 5$ dgts	
400mA	100 μ A	$\pm 1.0\% \pm 3$ dgts	$\pm 2.0\% \pm 5$ dgts	
4A	1mA	$\pm 1.0\% \pm 3$ dgts	$\pm 2.0\% \pm 5$ dgts	
40A	10mA	$\pm 1.0\% \pm 3$ dgts	$\pm 2.0\% \pm 5$ dgts	
60A (0-50A)	100mA	$\pm 1.5\% \pm 3$ dgts	$\pm 3.0\% \pm 5$ dgts	
60A (50 - 60A) ¹	100mA	$\pm 3.0\% \pm 5$ dgts	$\pm 3.5\% \pm 5$ dgts	

¹ Though the meter can display up to 400A, it is not calibrated beyond 60A.

AC Voltage:

(Input Impedance: 10M Ω)

Range	Resolution	Accuracy		Overload Protection
		50/60 Hz	40 - 1KHz	
400V	0.1V	$\pm 1.5\% \pm 2$ dgts	$\pm 2.0\% \pm 4$ dgts	AC 800V

Resistance (Ω) and Continuity:

(open voltage 0.4V)

Range	Resolution	Accuracy	Beeping	OL Protection
40-400 Ω	0.1 Ω	$\pm 1.0\% \pm 2$ dgts	< 38.0 Ω	AC 600V

General Specifications:

Conductor Size:	30mm max. (approx.)
Battery Type:	two 1.5V SUM-3
Display:	3 3/4 LCD with 40 seg. bargraph
Range Selection:	manual
Overload Indication:	OL
Power Consumption:	15 mA (approx.)
Low battery Indication:	
Sampling Time:	3 times/sec. (display) 30 times/sec. (bargraph)
Auto-Power-Off:	15 minutes
Operating Temperature:	-10°C to 50°C
Operating Humidity:	less than 85% relative
Storage Temperature:	-20°C to 60°C
Storage Humidity:	less than 75% relative
Altitude:	up to 2000M
Dimension:	210mm (L) x 62.0mm (W) x 35.6mm (H) 8.3" (L) x 2.4" (W) x 1.4" (H)
Weight:	200g (battery included)
Accessories:	Carrying bag x 1 Users manual x 1 1.5V battery x 2 Test leads x 1

PROVA INSTRUMENTS INC.

Add: 6F-2, No. 129, Lane 235, Pao-Chiao Road, Shin-Tien District,
New Taipei City 23145, TAIWAN

Tel: 886-2-89191255

Fax: 886-2-89191489

E-mail: prova@ms3.hinet.net

Website: www.prova.com.tw